








SPECTRUM Smoothing & Levelling Compounds

The **PROFESSIONALS**
First Choice

A range of compounds for smoothing, levelling, filling or patching

CODE	PRODUCT	DESCRIPTION	THICKNESS	CONSUMPTION	
NC 160 20kg		ECONOMIC SELF LEVELLING COMPOUND (Up to 20mm) APPLICATION: ▶ For smoothing and levelling prior to bonding textile and resilient coverings. ▶ Use on new substrates, e.g. cement screeds. ▶ Use on existing substrates in need of renovation. PROPERTIES: ▶ Easy to rub down. ▶ High strength. ▶ Interior use only. ▶ Cement and chromate free.	1mm 3mm 10mm	1.4 kg/m ² 4.2 kg/m ² 14.0 kg/m ²	
NC 170 20kg		HIGH STRENGTH, SELF SMOOTHING, MULTI-PURPOSE COMPOUND, ANY THICKNESS APPLICATION: ▶ For high quality smoothing and levelling work prior to all types of flooring installation. ▶ on new substrates, e.g. cement screeds. ▶ on existing sub-surfaces in need of refurbishment, e.g. on waterproof residues of adhesives and levelling compounds. PROPERTIES: ▶ Extremely good application characteristics. ▶ With Level Plus Effect thanks to high performance plasticiser technology. ▶ Very smooth surface. ▶ Very easy adhesive application. ▶ Up to 10% less adhesive consumption. ▶ Very good absorption capacity.	1mm 3mm 10mm	1.4 kg/m ² 4.2 kg/m ² 14.0 kg/m ²	
NC 182 20kg		LOW SLUMP, FINE CONSISTENCY, RAPID SETTING, ANY THICKNESS APPLICATION: ▶ Filling holes and surface damage. ▶ Levels adjustment and patch smoothing work. ▶ Fine skimming or area scratch-coating. ▶ All surfaces as a repair – filling and smoothing compound. PROPERTIES: ▶ From “nil” to thick coat application. ▶ Adjustable consistency. ▶ high speed construction product. ▶ Easy to rub down. ▶ Low chromate content.	1mm 3mm 10mm	1.5 kg/m ² 4.5 kg/m ² 15.0 kg/m ²	
NC 888 2 x 4.5kg		RAPID SKIM AND REPAIR COMPOUND (Up to 4mm) APPLICATION: ▶ New or old cement levelling compounds. ▶ Substrates with well bonded, water proof residues of adhesive & levelling compounds. ▶ Dense mineral substrates. ▶ Dry screed materials, chipboard & OSB board. ▶ All standard construction screeds, concrete etc. PROPERTIES: ▶ From a “feather edge” up to 4mm thickness. ▶ No primer required. ▶ Extremely rapid drying. ▶ Cement and chromate free. ▶ Excellent surface finish extended. ▶ Fine aggregate. ▶ Plastic drum is available for mixing powder.	1mm	1.4 kg/m ²	

MSDS's AVAILABLE ON REQUEST

N.B. We always recommend to prime – See page 2 for primers.