

Premium Office Solutions

# SPECTRUM VINYL SERIES 2

Value Engineered  
Flooring Systems

[spectrumfloors.com.au](http://spectrumfloors.com.au)

Phone : 1 300 786 585

Email : [admin@spectrumfloors.com.au](mailto:admin@spectrumfloors.com.au)



**spectrum**  
quality commercial flooring

BRISBANE | SYDNEY | MELBOURNE | HOBART | ADELAIDE | PERTH


# TECH DATA | 2 MM VINYL FLOORING

| SPECIFICATION         |                                       |                        | CLASSIFICATION           |                                    |                  |
|-----------------------|---------------------------------------|------------------------|--------------------------|------------------------------------|------------------|
| CONSTRUCTION          | Luxury Vinyl Tile with iGuard Surface |                        | BINDER CONTENT           | EN ISO 10585                       | Type 1.          |
| PLANK SIZE - WOOD     | EN ISO 24340                          | 186 x 1220 mm          | EUROPEAN CLASSIFICATION  | EN ISO 10582                       | Class: 33/42     |
| PLANK SIZE - STONE    | EN ISO 24346                          | 305 x 610 mm           | RESIDUAL INDENTATION     | EN ISO 24343                       | Max. 0.1 mm      |
| THICKNESS             | EN ISO 24346                          | 2.6 mm                 | DIMENSIONAL STABILITY    | EN ISO 23999                       | Max. 0.15%       |
| WEAR LAYER            | EN ISO 24340                          | 0.55 mm                | CURLING                  | EN ISO 23999                       | Max. 2 mm        |
| TOTAL WEIGHT          | EN ISO 23997                          | 40 kg/m                |                          |                                    |                  |
| PERFORMANCE           |                                       |                        |                          |                                    |                  |
| ABRASION GROUP        | MSZ EN 660-1                          | Class: T               | HYGIENE                  | Bacterial Resistant                |                  |
| FIRE RESISTANCE       | EN 13501-1                            | Class: Bfl-s1          | CASTOR CHAIR RESISTANCE  | EN426 / ISO 4918                   |                  |
| SLIP RESISTANCE       | EN ISO 13893                          | DS                     | ENVIRONMENTAL ATTRIBUTES | Solvent and Phthalate Free         |                  |
| ELECTRICAL PROPERTIES | EN 1816                               | Max. 2 kV / Antistatic | SURFACE TREATMENT        | iGuard PUR Surface / Easy Cleaning |                  |
| THERMAL RESISTANCE    | ISO 8302                              | 0.014 m2K/W            | CONTENT OF PCP           | EN 12673                           | Does Not Contain |
| LIGHT RESISTANCE      | EN ISO 105-80                         | Grade 6                | FORMALDEHYDE EMISSION    | ENV 717-1                          | E1 (no Emission) |
| CHEMICAL RESISTANCE   | EN ISO 26987                          |                        | VOC                      |                                    | Pass             |
|                       | ASTM F925                             |                        | CE MARKING               | EN 140041                          |                  |


**S610 White**




**S611 Mist**




**S612 Dusk**




**S614 Grey**




**S618 Charcoal**



**S622 Beige**




**S624 Coffee**



**S628 Terracotta**



**S670 Black**



**Installation** | Correct installation is an important part of a successful project. To facilitate the installation the underside of the covering is sanded. All products should be installed in accordance with BS 8203-2001 and good trade practice. Detailed laying instructions and water based non toxic adhesive recommendations are available on request.

**Maintenance** | Easy maintenance using environmentally safe materials to high European standards should be performed dependent on site conditions.  
Detailed cleaning instructions are available for each product on request.

**Complimentary technical advice and sample service available | For local personal service phone call 1300 786 585**  
**Please inquire with your Spectrum representative to ensure material availability | Allow 8-10 weeks delivery**

This information is correct at the time of printing 03/22 but the manufacturer reserves the right to carry out modifications aimed at product improvement without notice. NOTE: Due to manufacturing limitations, there may be variations between the colors of actual flooring and the samples shown in this brochure. © Spectrum Floors 2022